

GLOBAL JOURNAL OF RESEARCHES IN ENGINEERING: A MECHANICAL AND MECHANICS ENGINEERING Volume 14 Issue 8 Version 1.0 Year 2014 Type: Double Blind Peer Reviewed International Research Journal Publisher: Global Journals Inc. (USA) Online ISSN: 2249-4596 & Print ISSN: 0975-5861

### Simulation of Gear Dynamics by Circuit Theory Methods

### By Evgueni I. Podzharov, Jorge Alberto Torres Guillén & Julia Patricia Ponce Navarro

University of Guadalajara, Mexico

*Abstract-* A methodology of study of gear dynamics with the aid of the circuit theory and linear graph methods is presented. In terms of analogy of the force, electric tension is used for the composition of equivalent electrical circuit, which immediately gives the equations of motion. The application of the electrical analogy method for the automation of composition of equation of motion and their analysis are considered for the classical example of a one-stage gear transmission with flexible supports and coupling masses. This technique can be extended to analyse the dynamic characteristics of more complex dynamic systems as a planetary transmission with flexible supports.

*Keywords:* dynamic gear model, equivalent electric circuit, linear graph, node equations, automation of composition of motion equations.

GJRE-A Classification : FOR Code: 091399

## SIMULATION OF GEAR DYNAMICS BYCIRCUITTHEORYMETHODS

Strictly as per the compliance and regulations of:



© 2014. Evgueni I. Podzharov, Jorge Alberto Torres Guillén & Julia Patricia Ponce Navarro. This is a research/review paper, distributed under the terms of the Creative Commons Attribution-Noncommercial 3.0 Unported License http://creativecommons.org/licenses/by-nc/3.0/), permitting all non commercial use, distribution, and reproduction inany medium, provided the original work is properly cited.

# Simulation of Gear Dynamics by Circuit Theory Methods

Evgueni I. Podzharov<sup>a</sup>, Jorge Alberto Torres Guillén<sup>o</sup> & Julia Patricia Ponce Navarro<sup>P</sup>

Abstract- A methodology of study of gear dynamics with the aid of the circuit theory and linear graph methods is presented. In terms of analogy of the force, electric tension is used for the composition of equivalent electrical circuit, which immediately gives the equations of motion. The application of the electrical analogy method for the automation of composition of equation of motion and their analysis are considered for the classical example of a one-stage gear transmission with flexible supports and coupling masses. This technique can be extended to analyse the dynamic characteristics of more complex dynamic systems as a planetary transmission with flexible supports.

*Keywords: dynamic gear model, equivalent electric circuit, linear graph, node equations, automation of composition of motion equations.* 

#### I. INTRODUCTION

he classical method of Lagrange equation (Genkin and Grinkevich, 1961) and the methods of dynamic stiffness or admittance (Airapetov et al. 1975) are used in studies of gear dynamics. These methods are cumbersome and laborious. In order to automate composition of equations of motion, the bond graph (Karnopp and Rosenberg, 1972) and some other methods are also used. However, the use of these methods presupposes presentation of a dynamic model as a system with concentrated parameters. Also, the bond graph of a relatively simple model, as, for example, a planetary gear transmission, is very cumbersome (Allen, 1979). On the other hand, electrical analogy method (Skudrzyk, 1968) and linear graph method (Mason and Zimmermann, 1960) allow us to model dynamic systems with both concentrated and distributed parameters (Podzharov, 1983, 1987, Sasa et al., 2004, Wojnarowski, 2006, Kalous, 2009).

In this paper a methodology of study of gear dynamics with the aid of the electric circuit theory methods is presented. The analogy between the force and electric tension is used to compose equivalent electric circuits for dynamic gear systems.

Table 1 : Equivalent Parameters

No.	Mechanical System	Electrical System
1	Force	Tension
2	Speed	Electric current
3	Displacement	Electric charge
4	Mass	Inductance
5	Flexibility	Capacitance
6	Absorber	Electrical resistance

#### Nomenclature

 $J_i$  - moment of inertia of the mass  $m_i$ ,

- $k_i$  torsional stiffness
- $C_{s2}, C_{s3}$  support stiffnesses,

 $C_3$  - stiffness of tooth engagement,

 $T_1(t), T_2(t)$  - variable torsion moments,

 $\mu_i$  - moment of inertia reduced to the mass moving on the line of action,

 $C_i$ - torsion stiffness reduced to linear stiffness on the line of action,

 $r_{hi}$  - base radius of a gear,

 $F_i(t)$  - torsional moment reduced to a force applied in the line of action of gear engagement,

 $S_i(t)$  - kinematic error in the gear engagement,

 $y_{ii}$  - element of the matrix of mechanical conductance,

Y - matrix of mechanical conductance,

Z - mechanical impedance,

 $T_{ii}$  - transmission in a graph between the points *i* and *j*,

f - frequency,

$$j = \sqrt{-1}$$
.

#### II. MODELLING ONE-STAGE GEAR TRANSMISSION

We shall now consider the use of electrical analogy for the automation of composition of equations of motion and their analysis in the example of one-stage gear transmission with flexible supports and coupled masses. The mechanical model of the transmission is shown in Fig.1 and in Fig. 2, presenting the equivalent electrical circuit. Here, the parameters of the torsion

Author α σ ρ: University of Guadalajara, Eletromechanical Engineering Department, Av. Revolución 1500, Guadalajara, Jalisco, C.P., México. e-mail: epodzhar@up.edu.mx

(2)

system reduced to the parameters of a linear system are determined as follows:

$$\mu_{i} = J_{i} / r_{bi}^{2}, \ C_{ki} = k_{i} / r_{bi}^{2}, \ F_{i}(t) = T_{i}(t) / r_{bi}$$
(1)

This system has 10 independent elements and 11 resonances and antiresonances (Skudrzyk, 1968), including zero and infinite frequencies. When the circuit is excited by variable tensions (forces)  $F_1(t)$  and  $F_2(t)$  the contours  $C_1\mu_1$  and  $C_3\mu_4$  act as low frequency filters filtering out high frequency components. Thus, the existence of large coupled masses linked to the gears by relatively low stiffness shafts means that the gears are dynamically isolated from external excitation in medium and high frequency ranges.

Let us consider stationary vibrations and assume that the gear is a linear dynamic system. Then, the solution of this system with periodic force or kinematic excitation can be found as a sum of harmonics. In this case the equations of motion can be composed as Kirchhoff equations of the equivalent electric circuit.

The total conductance between the points *a* and *b* will be equal to the sum of the conductances of parallel branches (Skudrzyk, 1968).

 $Y_{ab} = Y_0 + Y_1 + Y_2 + Y_3 + Y_4,$ 

where

$$Y_{0} = j\omega/C_{2}, Y_{2} = (j\omega m_{2} + C_{S2} / j\omega)^{-1},$$

$$Y_{1} = \left[ \left( \frac{1}{j\omega \mu_{1}} + \frac{j\omega}{C_{1}} \right)^{-1} + j\omega \mu_{2} \right]^{-1},$$

$$Y_{3} = (j\omega m_{3} + C_{S3} / j\omega)^{-1},$$

$$Y_{4} = \left[ \left( \frac{1}{j\omega \mu_{4}} + \frac{j\omega}{C_{3}} \right)^{-1} + j\omega \mu_{3} \right]^{-1}.$$
(3)

The input impedance between points *a* and *b* can be found as inverse of  $Y_{ab}$ 

$$Z_{ab} = 1/Y_{ab}.$$
 (4)

Substituting the equations (3) in the equation (2) and (4) and making  $Z_{ab}$  equal zero, we can find a frequency characteristic of  $Z_{ab}$ , which is shown in Fig. 3 for the transmission with the following parameters:

$$\begin{split} J_1 &= 0.012 \ kg \ m^2, & J_2 &= 0.000686 \ kg \ m^2, \\ J_3 &= 0.00471 \ kg \ m^2, & J_4 &= 0.02 \ kg \ m^2, \\ m_2 &= 1.56 \ kg, & m_3 &= 3.8 \ kg, \\ C_{s2} &= 0.455 \cdot 10^8 \ N \ / \ m, & C_{s3} &= 0.101 \cdot 10^8 \ N \ / \ m, \end{split}$$

$$C_{s2} = 0.27 \cdot 10^9 \, N \,/\, m, \qquad k_1 = 4270 \, N \cdot m$$
  
$$k_3 = 2000 \, N \cdot m \,, \ r_{b2} = 0.0383 \, m, \ r_{b3} = 0.0634 \, m.$$

It was calculated neglecting the damping in the system and, according to the Foster theorem (Skudrzyk, 1968), it has a monotonous character. We can find from the curve that the poles are at frequencies 55 Hz, 209 Hz, 300 Hz, 794 Hz and 5200 Hz. The zeros are at the frequencies 115 Hz, 259.5 Hz, 408 Hz and 859.5 Hz.

The poles  $f_{pi}$  and zeros  $f_{sj}$  can also be found approximately from the concepts of parallel and successive resonances or resonances of tensions and currents:

$$f_{p1} = \frac{1}{2\pi} \sqrt{\frac{C_1}{\mu_4}} = 50 \ Hz \,, \tag{5}$$

$$f_{p2} = \frac{1}{2\pi} \sqrt{\frac{C_2 + C_{s2}}{\mu_3 + m_3}} = 232 \ Hz,$$

$$f_{p3} = \frac{1}{2\pi} \sqrt{\frac{C_{S1}}{m_2 + \mu_1 + \mu_2}} = 336 \ Hz \ , \qquad (7)$$

$$f_{p4} = \frac{1}{2\pi} \sqrt{\frac{C_1 + C_{s2}}{\mu_{23} + m_2}} = 778 \ Hz \,, \tag{8}$$

$$f_{p5} = \frac{1}{2\pi} \sqrt{C_2} \left( \mu_2^{-1} + \mu_3^{-1} + m_2^{-1} + m_3^{-1} \right) = 5162 \ Hz \quad (9)$$

$$f_{S1} = \frac{1}{2\pi} \sqrt{\frac{C_3}{\mu_3}} = 104 \ Hz \,, \tag{10}$$

$$f_{S2} = \frac{1}{2\pi} \sqrt{\frac{C_{S3}}{m_3}} = 259.5 \ Hz \ , \tag{11}$$

$$f_{S3} = \frac{1}{2\pi} \sqrt{\frac{C_1}{\mu_2}} = 397 \ Hz \,, \tag{12}$$

$$f_{S4} = \frac{1}{2\pi} \sqrt{\frac{C_{S2}}{m_2}} = 859.5 \ Hz \,, \tag{13}$$

As we see, the approximate and exact frequencies are very similar to each other. Therefore, the formulas (5) - (13) can be used for the analysis of resonances.

Now, let us use the linear graph method (Mason and Zimmermann, 1960) to obtain a general form for this model. A linear graph for the circuit in Fig. 2 is constructed in Fig. 4. This graph illustrates the relations between forces  $F_i$  (upper nodes) and velocities  $v_i$ (lower nodes). The lines between them are transmissions, which in this case are mechanical

(16)

admittances  $y_i$  or mechanical impedances  $z_i$ . Thus, in this graph we use relations

$$v_i = y_i \cdot F_i$$
 and  $F_i = z_i \cdot v_i$  (14)

In order to simplify the graph, the number of nodes can be reduced retaining only the nodes which we need to determine. Further simplification of the graph can be implemented by adding parallel transmissions and excluding the nodes, which we do not need to determine, by splitting them. Hence, splitting the nodes  $F_{\mu i}$ ,  $v_{Ci}$ ,  $v_{\mu i}$  and excluding the loops  $l_i$ , we can obtain the transformed graph presented in Fig. 5. Here,

$$y_{\mu i} = 1/(j\omega \mu_i), \ y_{Ci} = j\omega/C_i,$$
  
$$y_{Si} = 1/(j\omega \mu_i + C_i/(j\omega))$$
(15)

The transmissions of this graph can be determined by the following formulas

$$T_{11} = \frac{y_{\mu 1}}{y_{Ci}(1-l_1)}; \ T_{12} = \frac{y_{\mu 2}}{y_{Ci}(1-l_1)},$$
$$T_{21} = \frac{y_{\mu 2}}{y_{C2}(1-l_2)}, \ T_{22} = \frac{1}{y_{C2}(1-l_2)},$$
$$T_{23} = \frac{y_{\mu 3}}{y_{C2}(1-l_2)}, \ T_{32} = \frac{y_{\mu 3}}{y_{C3}(1-l_3)},$$
$$T_{33} = \frac{y_{\mu 4}}{y_{C2}(1-l_2)}.$$
(1)

Where

$$l_{1} = -(y_{\mu 1} + y_{\mu 2}) / y_{C1}, \ l_{3} = -(y_{\mu 3} + y_{\mu 4}) / y_{C3},$$
$$l_{2} = -(y_{\mu 2} + y_{\mu 3} + y_{s2} + y_{s3}) / y_{C2}.$$
(17)

This graph can also be described by the equations determining the nodes in relation to adjacent nodes and transmissions that link them:

$$F_{C1} - T_{12}F_{C2} = T_{11}F_{1}(t)$$
  
$$-T_{21}F_{C1} + F_{C2} - T_{23}F_{C3} = T_{22}\dot{S}_{2}(t)$$
(18)  
$$-T_{32}F_{C2} + F_{C3} = T_{33}F_{4}(t)$$

Substituting (16) and (17) in (18) and multiplying each of the *t*ch equation (18) by  $y_{Ci}(1-l_i)$ , we have

$$y_{11}F_{C1} - y_{12}F_{C2} = y_{\mu 1}F_{1}(t)$$
  
-  $y_{21}F_{C1} + y_{22}F_{C2} - y_{23}F_{C3} = \dot{S}_{2}(t)$  (19)

$$-y_{32}F_{C2} + y_{33}F_{C3} = F_4(t)$$

Where  $y_{11} = y_{C1} + y_{\mu 1} + y_{\mu 2}$ ,  $y_{12} = y_{21} = y_{\mu 2}$ ,

$$y_{22} = y_{C2} + y_{\mu 2} + y_{\mu 3} + y_{S2} + y_{S3} , \qquad (20)$$

$$y_{23} = y_{32} = y_{\mu3}, \ y_{33} = y_{C3} + y_{\mu3} + y_{\mu4}.$$

As we can see from equation (19) and (20), equation (19) has the form

$$Y \times F_c = P , \qquad (21)$$

Here, the matrix of the mechanical conductance Y is symmetrical; each itch diagonal element is positive and equal to the sum of the input mechanical conductances of the elements, which enter the itch node. Each non-diagonal element is negative and equal to the transition conductance of the elements, which locate between itch and *j*-th nodes. This type of matrix is known in the circuit theory as matrix of node equations (Karni, 1966).

The excitation term in the right-hand part of the *i*-th equation is equal to the velocity of cinematic error in the gear engagement, in the case of cinematic excitation. In the case of force excitation, it equals to the product of the exciting force and the transition conductance between the point of application of the force and the itch node.

Therefore, it is not necessary to compose equivalent electric circuits and graphs. Instead, following the rules explained above, we can directly compose the matrix of mechanical conductance and the vector of the right-hand part of the equations.

The above formulated rules can be extended to more complicated systems and systems with distributed parameters.

A dynamic calculation of the gear with the parameters mentioned above was implemented using the equations (15) – (20). The damping in elastic elements was considered by introducing complex stiffness (Skudrzyk, 1968).

$$\overline{C}_i = C_i (1 + j \eta_i), \qquad (22)$$

Where  $\eta_i$  - loss factor in *i*-th elastic element.

The results of calculation of dynamical forces  $F_{Ci}$  in elastic elements are presented in Fig.6; the amplitude of kinematic excitation  $\dot{S}_2 = 5 \ \mu m$  and the loss factor in all of the elastic elements was taken equal to 0.1. As we see from the graph, in the low frequency range the dynamic forces in each elastic element are the same. The resonance at the frequency 55 Hz corresponds to the frequency of natural vibrations of mass  $\mu_4$  at the stiffness  $C_3$ , and the high frequency of

vibrations of all masses at the stiffness  $C_2$  of the gear engagement. The origin of all other resonances can be checked with the aid of equations (5) - (9).

The measurement of noise and vibration of this gear shows that it has high levels at frequency 5200 Hz.

#### **CONCLUSIONS** III.

- a) The use of electric analogy allows us to avoid the derivation of equations of motion and to make a frequency analysis without solving the equations.
- b) Equations analogous to node equations known in the circuit theory can be used in the gear dynamics for the systems with concentrated and distributed parameters.
- There is no need to compose any electric circuit and C) linear graph to obtain linear equations of motion of a dynamic system. They can be composed as node equations directly for a dynamic model.

#### **References** Références Referencias

- 1. Airapetov E.L. et al., Computer Using for Calculation of Multilink Dynamic Systems by the Method of Dynamic Stiffness. In: Solutions of Mechanical Problems by Computer. Ed. by N.G. Bruevich and V.I. Sergeev. Moscow, 1975, 42-47.
- 2. Allen R.R., "Multiport models for the kinematic and dynamic analysis of gear power transmissions". Journal of Dynamical Design and Technology, 101(2), 1979, 43-53.

- Bond graph modeling for engineering systems. Ed. З. by Karnopp D. and Rosenberg R. New York, 1972, 95 p.
- Genkin M.D., Grinkevich V.K., Dynamic Loads in the 4. Transmission with Helical Gears. Ed. Academy of Science of the USSR, 1961, 119 p.
- 5. Jaroslav Kalous, "Program SNAP A tool for electromechanical drives analysis". Engineering Mechanics, 16(4), 2009, 251-264.
- 6. Karni Sh., Network Theory: Analysis and Synthesis. Allyn and Bacon, Inc., 1966, 368 p.
- 7. Mason S.J., Zimmermann H.J., Electronic Circuits, Signals, and Systems. John Wiley and Sons, Inc., 1960, 619 p.
- 8. Podzharov E. I., "Research on gear dynamics with the aid of circuit theory method". Izvestia Vysshih Uchebnych Zavedenii. Mashinostroenie, 5, 1983, 41-45.
- Podzharov E. I., "Graphic modelling of the dynamic 9. performance of multi-stage gear transmissions". Soviet Engineering Research, 7(7), 1987, 34-36.
- 10. Sasa, L. Mcphee J., Schmitke G., et al, "A comparison of different methods for modeling electromechanical multibody systems". Multibody System Dynamics, 12(3), 2004, 209-250.
- 11. Skudrzyk E., Simple and Complex Vibratory Systems. The Pennsylvania State University Press, 1968, 557 p.
- 12. Wojnarowski J., Kopec J., Zawislak S., "Gears and graphs". Journal of Theoretical and Applied Mechanics, 44(1), 2006, 139-162.







Fig. 3 : Frequency characteristic of input impedance











Fig. 6 : Dynamic loads in the gear